



2-conductor ground terminal block; 2.5 mm²; suitable for Ex e II applications; side and center marking; for DIN-rail 35 x 15 and 35 x 7.5; Push-in CAGE CLAMP®

Item No.: 2002-1207



2-conductor ground terminal block; 2.5 mm²; suitable for Ex e II applications; side and center marking; for DIN-rail 35 x 15 and 35 x 7.5; Push-in CAGE CLAMP®

Marking

RoHS ✓
Compliant

Business data

| | |
|----------------------|---------------|
| Supplier | WAGO |
| Item no. | 2002-1207 |
| GTIN / EAN | 4017332999212 |
| Content | 1 |
| Order amount | 100 |
| Customer item number | |

Notes

Technical data

Miscellaneous


| | |
|---------------------------------|---------------------|
| Ratings per | IEC/EN 60947-7-2 |
| Connection technology | Push-in CAGE CLAMP® |
| Actuation type | Push-in |
| Connectable conductor materials | Copper |
| Nominal cross section | 2.5 mm ² |



Printview: 2-conductor ground terminal block; 2.5 mm²; suitable for Ex e II applications; side and center marking; for DIN-rail 35 x 15 and 35 x 7.5; Push-in CAGE CLAMP® - Item No.: 2002-1207

| Technical data | |
|---|--|
| <i>Solid conductor</i> | <i>0.25 ... 4 mm² / 22 ... 12 AWG</i> |
| <i>Solid conductor, push-in termination</i> | <i>0.75 ... 4 mm² / 18 ... 12 AWG</i> |
| <i>Fine-stranded conductor</i> | <i>0.25 ... 4 mm² / 22 ... 12 AWG</i> |
| <i>Fine-stranded conductor with ferrule, push-in termination, f</i> | <i>0.75 mm² / 18 AWG</i> |
| <i>Strip length</i> | <i>10 ... 12 mm / 0.39 ... 0.47 Inch</i> |
| <i>Total number of connection points</i> | <i>2</i> |
| <i>Total number of potentials</i> | <i>1</i> |
| <i>Number of levels</i> | <i>1</i> |
| <i>Type of wiring</i> | <i>Front-entry wiring</i> |
| <i>Width</i> | <i>5.2 mm / 0.205 Inch</i> |
| <i>Height from upper-edge of DIN-35 rail</i> | <i>32.9 mm / 1.295 Inch</i> |
| <i>Depth</i> | <i>50.8 mm / 2 Inch</i> |
| <i>Design</i> | <i>horizontal</i> |
| <i>Type of mounting</i> | <i>Carrier rail 35 x 15</i> |
| <i>Marking level</i> | <i>Center/side marking</i> |
| <i>Color</i> | <i>green-yellow</i> |
| <i>Insulating material</i> | <i>Polyamide 66 (PA 66)</i> |
| <i>Fire load [MJ]</i> | <i>0.087 [MJ]</i> |
| <i>Weight [g]</i> | <i>7.706 [g]</i> |
| <i>Packaging type</i> | <i>BOX</i> |
| <i>Product Family</i> | <i>TOPJOB® S</i> |
| <i>Main product function</i> | <i>GND cond. term. block</i> |
| <i>Product type</i> | <i>Through rail-mount term. blocks</i> |

Printview: 2-conductor ground terminal block; 2.5 mm²; suitable for Ex e II applications; side and center marking; for DIN-rail 35 x 15 and 35 x 7.5; Push-in CAGE CLAMP® - Item No.: 2002-1207

Images & drawings





Address

WAGO Kontakttechnik GmbH & Co. KG

Hansastr. 27

32423 Minden

Telefon: 0571/887-0

Fax: 0571/887-169

<http://www.wago.com>

© WAGO Kontakttechnik GmbH & Co. KG

Technische Änderungen und Irrtümer vorbehalten.