



### Main

|                                    |                      |
|------------------------------------|----------------------|
| Range                              | Resi9                |
| Product or component type          | Comb busbar          |
| Accessory / separate part category | Connection accessory |
| Lines description                  | 1L                   |
| Total number of 18 mm modules      | 57                   |

### Complementary

|                                |   |
|--------------------------------|---|
| Number of ways                 | 57 ways 1 L   |
| Poles configuration for 1 way  | 1 x 1P  |
| Connection pitch               | 18 mm   |
| Connector type                 | Fork  |
| Distance between way           | 18 mm   |
| Marking                        | L   |
| Insulation                     | Insulated   |
| Device presentation            | Cuttable  |
| [Ie] rated operational current | 63 A ( 40 °C )  |
| [Ue] rated operational voltage | 230 V AC Ph/N   |
| [Ui] rated insulation voltage  | 500 V AC  |
| Mounting mode                  | Horizontal  |
| Mounting location              | Bottom on biconnect   |
| 9 mm pitches                   | 114   |
| Width                          | 1000 mm   |
| Colour                         | Light grey ( RAL 7035 )   |
| Range compatibility            | Acti 9 K60<br>Resi9 MCB<br>Resi9 RCBO<br>Resi9 RCCB<br>Resi9 SWITCH |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Environment

|                        |   |
|------------------------|---|
| Standards              | IEC 61439-2<br>IEC 60947-7-1                |
| Product certifications | CE  |
| Fire resistance        | 960 °C ( 30 s ) conforming to IEC 60695-2-1 |
| Pollution degree       | 3   |

## Offer Sustainability

|                                  |   |
|----------------------------------|---|
| Sustainable offer status         | Green Premium product   |
| RoHS (date code: YYWW)           | Compliant - since 1329 - Schneider Electric declaration of conformity<br><a href="#">Schneider Electric declaration of conformity</a> |
| REACH                            | Reference not containing SVHC above the threshold<br><a href="#">Reference not containing SVHC above the threshold</a>                |
| Product environmental profile    | Available<br><a href="#">Product environmental</a>  |
| Product end of life instructions | Need no specific recycling operations   |

## Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|