

# PLASTIC DISTRIBUTION BOARDS GREY DOOR



## MAIN TECHNICAL FEATURES

- Resistance: Chemical agents, alkali, oils, salts, etc.
- Rated Voltage: Up to 690V
- Maximum Current: Up to 800A
- Operating Temperature: -35°C + 65°C
- Material: HB ABS Halogen Free
- Mounting Plate: Galvanised steel 1mm
- IP Degree: IP65
- IK Degree: IK08
- Colour: RAL7035 Grey (Other colours on request)
- **CE** RoHS



HALOGEN  
FREE

 IP65

**CE**

## PLASTIC DISTRIBUTION BOARDS - GREY DOOR

| CODE   | L (mm) | W (mm) | H (mm) | WEIGHT(kg) |
|--------|--------|--------|--------|------------|
| PP3001 | 200    | 300    | 130    | 1.80       |
| PP3002 | 250    | 350    | 150    | 2.40       |
| PP3004 | 300    | 400    | 170    | 3.00       |
| PP3005 | 300    | 400    | 220    | 3.40       |
| PP3006 | 350    | 500    | 190    | 4.35       |
| PP3003 | 400    | 500    | 175    | 4.50       |
| PP3007 | 400    | 500    | 240    | 5.40       |
| PP3008 | 400    | 600    | 200    | 5.85       |
| PP3010 | 500    | 700    | 250    | 9.70       |
| PP3021 | 600    | 800    | 260    | 10.80      |