



Main

Range	Resi9
Product or component type	Comb busbar
Accessory / separate part category	Connection accessory
Lines description	3L
Total number of 18 mm modules	57

Complementary

Number of ways	19 ways 3 L
Poles configuration for 1 way	1 x 3P
Connection pitch	18 mm
Connector type	Fork
Distance between way	54 mm
Marking	L1 L2 L3
Insulation	Insulated
Device presentation	Cuttable
[Ie] rated operational current	63 A (40 °C)
[Ue] rated operational voltage	400 V AC Ph/Ph
[Ui] rated insulation voltage	500 V AC
Mounting mode	Horizontal
Mounting location	Bottom on biconnect
9 mm pitches	114
Width	1000 mm
Colour	Light grey (RAL 7035)
Range compatibility	Acti 9 K60 Resi9 MCB Resi9 RCBO Resi9 RCCB Resi9 SWITCH

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environment

Standards	IEC 61439-2 IEC 60947-7-1
Product certifications	CE
Fire resistance	960 °C (30 s) conforming to IEC 60695-2-1
Pollution degree	3

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1329 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available Product environmental
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------