

T **TEHNOPLAST**
CE IP65 AC400V

series **d**

ENCLOSURES IP65 – SURFACE MOUNTING


series d



name	N4D	N8D	N12D	N24D	N36D
type	IP 65 □ In 63A	IP 65 □ In 63A	IP 65 □ In 63A	IP 65 □ In 63A	IP 65 □ In 63A
dimensions	128 x 201 x 120	202 x 201 x 120	319 x 259 x 144	319 x 384 x 144	319 x 508 x 144
no. of modules	4	8	12	24	36
PE, N terminal	2 x 4	2 x 8	2 x 10	2 x 13	2 x 15



PLASTIC ENCLOSURE WITH PLASTIC DOOR



Plastic holder keeps the terminals on the position

Enclosures are completely assembled with all necessary part, such as:

- DIN rail
- Insulated terminals, neutral and ground
- Cover for blank space
- Needed installation accessories
- Plastic cap for screws
- Manual instruction
- * *Additional terminal upon request*

series d

	A	B	C	D	E	F
N4D	201 mm	128 mm	120 mm	-	78 mm	111 mm
N8D	201 mm	202 mm	120 mm	-	100 mm	140 mm
N12D	259 mm	319 mm	144 mm	-	210 mm	130 mm
N24D	384 mm	319 mm	144 mm	125 mm	210 mm	255 mm
N36D	508 mm	319 mm	144 mm	125 mm	210 mm	380 mm

Material	Acrylonitrile acrylic styrene
Color	RAL 7035
Door	Polycarbonate
Color	Transparent
Glow wire test	650°C
Terminal holder	Self extinguish material
Glow wire test	960°C
Temperature	-25°C / +60°C
Rated voltage	AC400V / DC 1000V
According to	IEC 60670 / IEC 60228
UV stable	Yes
Halogen free	Yes

